



减速箱参数 Gearbox Specifications

减速比 (Reduction)		3.25	10.56	16	34.33	64	111.57	208
		4	13		42.25		137.31	256
					52		169	
级数 (Number of stages)		1	2		3		4	
最大连续转矩 (Max. continuous torque)	Nm	0.01	0.025		0.03		0.05	
堵转转矩 (Stall torque)	Nm	0.02	0.05		0.08		0.1	
最大效率 (Max. efficiency)	%	90	80		70		60	
减速箱长度 (Gearbox length)	mm	10.8	13.8		16.8		19.8	
空载回差 (No load backlash) (MT版数据)	°	2	3		3		4	
重量 (Weight)	g	5.5	7		8.5		10	

技术参数 Technical Parameters

输出端轴承 (Bearing at output)	滚珠轴承 Ball bearings
径向间隙 (距法兰12mm处) (Radial play, 12mm from flange)	≤0.1mm
轴向间隙 (Axial play at axial load)	≤0.2mm
推荐输入转速 (Recommended input speed)	≤8000rpm
推荐温度范围 (Recommended temperature range)	-10...+60°C
允许安装力 (Force for press fits)	≤10N
径向负载 (距法兰12mm处) (Radial load, 12mm from flange)	≤5N
轴向负载 (Axial load)	≤5N