



减速箱参数 Gearbox Specifications

减速比 (Reduction)		4	16	27.04	64	140.6	256	562.4
		5.2	20.8		83.2		332.8	731.12
级数 (Number of stages)		1	2		3		4	
					108.16		432.64	
最大连续转矩 (Max. continuous torque)	Nm	0.2	0.2		0.3		0.35	
堵转转矩 (Stall torque)	Nm	0.3	0.3		0.45		0.5	
最大效率 (Max. efficiency)	%	90	80		70		60	
减速箱长度 (Gearbox length)	mm	14.9	19		23.1		27.2	
空载回差 (No load backlash) (MT版数据)	°	2	3		3		4	
重量 (Weight)	g	20	24		28		32	

技术参数 Technical Parameters

输出端轴承 (Bearing at output)	滚珠轴承 Ball bearings
径向间隙 (距法兰12mm处) (Radial play, 12mm from flange)	≤0.1mm
轴向间隙 (Axial play at axial load)	≤0.2mm
推荐输入转速 (Recommended input speed)	≤10,000rpm
推荐温度范围 (Recommended temperature range)	-10...+60°C
允许安装力 (Force for press fits)	≤10N
径向负载 (距法兰12mm处) (Radial load, 12mm from flange)	≤8N
轴向负载 (Axial load)	≤10N